

999.00 EUR

incl. 19% VAT, plus [shipping](#)

- Slot-In !



- Slim type Slot Loading design
- Buffer underrun Prevention
- Supporting disc-at-once, session-at-once, packet write, incremental, over write, track-at-once recording mode, sequential write, multi-session, and back ground format
- Horizontal and vertical mounting for most system configuration
- Emergency Eject Function

Write Speed

DVD+R 8x (ZCLV), 3x (CLV)
 DVD+R DL 6x (ZCLV), 3x (CLV)
 DVD-R 8x (ZCLV), 3x (CLV)
 DVD-R DL 6x (ZCLV), 3x (CLV)
 DVD+RW 8x (ZCLV), 3x (CLV)
 DVD-RW 6x (ZCLV), 3x (CLV)
 DVD-RAM 5x (PAV), 3x (CLV), 2x (CLV)
 CD-R 24x (ZCLV), 10x (CLV)
 CD-RW US+ 16x (ZCLV), 10x (CLV)
 US 24x (ZCLV), 10x (CLV)
 HS 10x (CLV)
 MS 4x (CLV)

Read Speed

DVD-ROM 8x (CAV)
DVD±R 8x (CAV)
DVD±R DL (Finalized Disc) 8x (CAV)
DVD-RAM (4.7G) 5x (CAV)
CD-ROM 24x (CAV)
CD-R 24x (CAV)
CD-RW 24x (CAV)
CD-DA (DAE) 24x (CAV)

Disc Diameter 12cm, 8cm

Interface SerialATA Revision 2.6

Data Transfer Rate Gen1 1.5GB/sec

Access Time 130ms (typ) DVD-ROM, 130ms (typ) CD-ROM

Data Buffer 2MB

Loading Mechanism Slot Loading Type

Scope of supply:

- Teac DV-W28SS drive
- SlimSATA-to-SATA Adapter